


Geberit Silent-db20 bend



Example image



Application purposes

- For building drainage
- For buildings with increased sound insulation requirements

Characteristics

- Can be shortened
- Long leg
- Abrasion resistant

- Highly sound-insulating
- UV-resistant

Technical data

Storage temperature (°C) - min. to max.	≤ 40 °C
Product material	PE-S2
Thermal expansion (mm/(m·K))	0.17 mm/(m·K)
Thermal conductivity, pipe (W/(m·K))	0.43 W/(m·K)

Art. no.	DN / nominal width	d, ø / outer diameter r (mm)	arc / angle (°)	X / leg length / L-dimension (cm)	X1 / leg length / L-dimension (cm)	K / cutting (cm) - max.
305.150.14.1	56	56 mm	15 °	7.5 cm	4.5 cm	3.5 cm
306.150.14.1	60	63 mm	15 °	7.5 cm	5 cm	3.5 cm
307.150.14.1	70	75 mm	15 °	8 cm	5 cm	3.5 cm
308.150.14.1	90	90 mm	15 °	10 cm	5.5 cm	5.5 cm
310.150.14.1	100	110 mm	15 °	10 cm	6 cm	5.5 cm
315.150.14.1	150	160 mm	15 °	13 cm	7.5 cm	8 cm
305.300.14.1	56	56 mm	30 °	7.5 cm	4.5 cm	3.5 cm
306.300.14.1	60	63 mm	30 °	7.5 cm	5 cm	3 cm
307.300.14.1	70	75 mm	30 °	8 cm	5 cm	3.5 cm
308.300.14.1	90	90 mm	30 °	10 cm	6.5 cm	4.5 cm
310.300.14.1	100	110 mm	30 °	10 cm	6 cm	4.5 cm
315.300.14.1	150	160 mm	30 °	15.7 cm	15.7 cm	7 cm
305.450.14.1	56	56 mm	45 °	7.5 cm	4.5 cm	3 cm
306.450.14.1	60	63 mm	45 °	7.5 cm	5 cm	2.5 cm
307.450.14.1	70	75 mm	45 °	8 cm	5 cm	2.5 cm
308.450.14.1	90	90 mm	45 °	10 cm	5.5 cm	4 cm
310.450.14.1	100	110 mm	45 °	10 cm	6 cm	4 cm
315.450.14.1	150	160 mm	45 °	15.5 cm	9.5 cm	8 cm
305.670.14.1	56	56 mm	67 °	7.5 cm	5.5 cm	2 cm
307.670.14.1	70	75 mm	67 °	8 cm	6 cm	2 cm
308.670.14.1	90	90 mm	67 °	10 cm	7 cm	3 cm
310.670.14.1	100	110 mm	67 °	10 cm	8 cm	2.5 cm