


Geberit Silent-PP branch fitting 87.5°



Example image



Application purposes

- For draining off waste water within buildings

Characteristics

- Acoustically optimised
- Seal made of EPDM

Technical data

Installation temperature (°C) - min. to max.	-10 – +40 °C
Product material	PP-MD
Thermal expansion (mm/(m·K))	0.08 mm/(m·K)

Art. no.	DN / nominal width	d, ø / outer diameter (mm)	d1, ø / outer diameter (mm)	arc / angle (°)	H / height (cm)	Z1 / Z-dimension (cm)	Z2 / Z-dimension (cm)	Z3 / Z-dimension (cm)
390.046.14.1	30	32 mm	32 mm	87.5 °	8.2 cm	1.7 cm	2.1 cm	2.1 cm
390.147.14.1	40	40 mm	40 mm	87.5 °	9.2 cm	2.2 cm	2.2 cm	2.2 cm
390.247.14.1	50 / 40	50 mm	40 mm	87.5 °	9.5 cm	2.2 cm	2.8 cm	2.2 cm
390.248.14.1	50	50 mm	50 mm	87.5 °	10.5 cm	2.7 cm	2.8 cm	2.8 cm
390.347.14.1	70 / 40	75 mm	40 mm	87.5 °	10.4 cm	2.3 cm	4.2 cm	2.6 cm
390.348.14.1	70 / 50	75 mm	50 mm	87.5 °	11.4 cm	2.8 cm	4.2 cm	3.1 cm
390.349.14.1	70	75 mm	75 mm	87.5 °	13.9 cm	4 cm	4.3 cm	4.3 cm
390.448.14.1	90 / 50	90 mm	50 mm	87.5 °	12.1 cm	2.8 cm	4.9 cm	3.2 cm
390.449.14.1	90 / 70	90 mm	75 mm	87.5 °	14.6 cm	4 cm	5.1 cm	4.5 cm
390.547.14.1	100 / 40	110 mm	40 mm	87.5 °	12.4 cm	2.7 cm	6 cm	2.9 cm
390.548.14.1	100 / 50	110 mm	50 mm	87.5 °	12.9 cm	2.8 cm	6 cm	3.2 cm
390.549.14.1	100 / 70	110 mm	75 mm	87.5 °	15.4 cm	4 cm	6.1 cm	4.5 cm
390.650.14.1	125 / 90	125 mm	90 mm	87.5 °	17.1 cm	4.6 cm	6.9 cm	5.2 cm
390.651.14.1	125 / 100	125 mm	110 mm	87.5 °	21.3 cm	6.6 cm	7.8 cm	7.3 cm
390.652.14.1	125	125 mm	125 mm	87.5 °	20.6 cm	6.4 cm	6.8 cm	6.8 cm
390.751.14.1	150 / 100	160 mm	110 mm	87.5 °	19.8 cm	5.5 cm	8.8 cm	6.2 cm
390.752.14.1	150 / 125	160 mm	125 mm	87.5 °	21.3 cm	6.4 cm	8.7 cm	6.9 cm
390.753.14.1	150	160 mm	160 mm	87.5 °	24.8 cm	8.2 cm	8.6 cm	8.6 cm